

## BARREDORA ANGULABLE








**DYNAMAQ - VB S.A.**

Avigiras E13-140Y Guayacanes. Urbanización Jardines de Amagasi 171, Quito, Ecuador

Tel. (593) 99 586 7799 · fvasquez@dynamaq.com · [www.dynamaq.com](http://www.dynamaq.com)

# CARACTERÍSTICAS TÉCNICAS

Modelo	um	SA 155	SA 180	SA 210	SA 220	SA 240	SA 260
Ancho de trabajo	mm	1550	1800	2100	2200	2400	2600
Ancho total	mm	1670	1920	2220	2330	2560	2760
Caudal aceite mín-máx	l/min	30 - 40	30 - 50	50 - 90	70 - 100	90 - 130	100 - 140
Presión aceite mín-máx	bar	160 - 240		180 - 240		190 - 250	
Peso dotación estándar	kg	280	310	360	620	660	690
Material del cepillo	secciones sustituibles de polipropileno						
Cepillo	Ø mm	550 x n.34	550 x n.39	550 x n.46	800 x n.49	800 x n.53	800 x n.58
Angulación mecánica <sup>(1)</sup>		± 30°					
A	mm	365	475	605	917	1011	1091
B	mm	975	1085	1215	1353	1447	1527
C	mm	1340	1560	1820	2270	2458	2618
	t	2,0 - 2,8	2,3 - 3,5	3,5 - 4,8	---	---	---
	t	2,0 - 3,0	2,8 - 4,4	4,0 - 5,6	5,8 - 8,0	7,5 - 12,0	
	t	2,0 - 3,5	2,9 - 4,5	4,2 - 6,2	7,0 - 9,0	8,0 - 10,0	
	t	---	4,0 - 5,0	4,5 - 6,0	5,5 - 8,0	7,5 - 12,0	

Dimensiones de la máquina sin accesorios			A cm	B cm	C cm	SA 155	SA 180	SA 210	SA 220	SA 240	SA 260
		A	B	167	64	120	192	64	120	225	87
	B	C	64	120	120	192	120	225	233	256	276
	C		120	120	120	192	120	225	233	256	276

<sup>(1)</sup> Opcional hidráulica

